



LUBRICANTS

POWER TO PERFORM

HP MILCY POWER

Premium Quality Multi-grade Diesel Engine Oil

DESCRIPTION

HP MILCY POWER is a premium quality multi-grade diesel engine oil designed to provide excellent engine lubrication in turbo-charged as well as naturally aspirated diesel engines. Formulated with highly hydroprocessed base oils and carefully selected additive chemistry, HP MILCY POWER is designed to provide exceptional viscosity/temperature characteristics, unmatched engine protection, excellent load carrying ability, superior TBN retentivity and high soot dispersancy required for Turbo-charged engines. HP Milcy Power is available in 15W 40 viscometrics.

APPLICATIONS

All kinds of diesel engine (both turbo-charged & naturally aspirated) in commercial vehicles, utility vehicles, cars & jeeps, earth moving & construction equipments, DG sets requiring high quality heavy duty diesel engine oil.

FEATURES & BENEFITS

- Prolonged engine life
- Excellent soot dispersancy and sludge control
- Unmatched TBN retentivity
- Long drain interval
- Reduced oil consumption & better fuel economy

APPROVALS

All major Automotive manufactures viz. TATA, Ashok Leyland approves HP MILCY POWER for their Diesel Engines.

MEETS OR EXCEEDS REQUIREMENTS OF

- API CF-4
- HP MILCY POWER has been accredited with API CF-4 donut by API
- MB 228.1
- CCMC D-4/G-4/PD-2
- MIL-L-2104E
- Allison C-4



LUBRICANTS

POWER TO PERFORM

HP MILCY POWER

Premium Quality Multi-grade Diesel
Engine Oil

PHYSICO-CHEMICAL PROPERTIES

Kinematic Viscosity, cSt @ 100°C	14.0 – 15.2
Viscosity Index, min	120
Flash point (COC), °C, min	190
Pour Point, °C, Max.	-21
Sulphated Ash, % wt, Max	1.52
TBN, mg KOH/gm, min	9